



CUTTING-EDGE TECHNOLOGY



MOBILE SECURITY ODS 8000S TRAILER

- Intruder Detection and Alerting System
- Multi Level Deterrence
- Mobile Surveillance With Wireless Connectivity
- Solar and Hybrid Powered
- Quality guarantee + 2 years Warranty
- Optional Luxriot EVO-S VMS

RAPID DEPLOYMENT SURVEILLANCE SYSTEM

ODS 8000 Mobile surveillance trailer can be deployed in minutes.

HEAVY DUTY ROBUST TRAILER

8'x5' Heavy Duty Custom Trailer with 3000 Lbs Axle and 15 Inch wheels. Four leveling jacks on Outriggers plus one wheeled Jack, for easy deployment. Removable tongue allows smaller footprint and protection from vandalism.

SOLAR-POWERED LONG-LASTING BATTERY

Powered by Sun, with durable battery providing 3+ days of battery autonomy.

WIRELESS CONNECTIVITY AND REMOTE HEALTH MONITORING

Standard equipment includes dual SIM rugged 4G Router with WIFI & GPS. An onboard computer provides electrical health of the unit, as well as allows remote software update capability.

Optional Items:

- 5G Router
- Point-2-Point Bridge





ODS 8000 S MOBILE SURVEILLANCE TRAILER



SECURITY REINFORCEMENT FOR VARIOUS SITUATIONS

Great for short-term or long-term deployment and can operate independently with built in VMS, as well as tie into existing security infrastructure. Ideally suited for security and monitoring of construction sites, event centers, exploration fields, security outposts, parking lots, and more. It's powered by intelligent recording, night vision, and intruder detection. Blue flashing lights (dusk till dawn), Loud Siren and Red Beacon (triggered by event) as well as Tamper switch (triggered on opening of enclosure) are standard on all ODS 8000S.

Optional Item: 2 Way IP Speaker allowing engagement of monitoring

HYBRID HIGHLIGHTS

Allows long unattended deployment in areas with limited sunlight.

Full automation of starting and stopping of generator to maintain battery charge level for several weeks in heavy overcast and rainy weather.

The onboard computer provides full remote monitoring of electrical health of the unit.

MECHANICAL SPECS

Tow ball Size: 1 7/8"

Length with tongue: 78"

Width (folded condition): 55"

Width (PV extended): 72"

Height (mast extended): 135"

Height (mast with long neck extension): 180"

Height (folded condition): 90"

Weight: 700 ~ 950 Lbs. (variation in models)

SOLAR & BATTERY SPECS

WATTAGE: 800 / 1000 WATTS

BATTERY OPTIONS: 7.2 kWh, 9.6 kWh, 12.5 kWh

Deep Cycle Maintenance Free AGM or LiFePO4



CONTACT US

CALL +1 346-295-8900 | WWW.RISEUPTEC.COM

SALES@RISEUPTEC.COM

ADDRESS: 3115 FRY RD., SUITE #503 & 505 KATY, TX 77449